



Notes:
Unless Otherwise Specified

1. MATERIALS:
1.00 SQ. ALUMINUM, 6061-T6 (rROUND CORNERS)
2. PROCESS:
 1. CUT PART PER PRINT
 2. DRILL AND MILL PART PER PRINT
 3. INSPECTION #1
 4. CLEAR ANODIZE, MIL-A-8625F C2
 5. INSPECTION #2
3. FINISH: ALUMINUM/SILVER
4. DEBURR ALL SHARP CORNERS AND EDGES

| | | | |
|--------------------------------------|--|--|--|
| UNLESS OTHERWISE SPECIFIED: | | TITLE: CBL-00 Rigging Connector Bar | |
| DIMENSIONS ARE IN INCHES | | NEXT ASSY: | |
| TOLERANCES: | | USED ON: | |
| FRACTIONAL: $\pm 1/64$ | | SIZE | |
| ANGULAR: MACH $\pm 5^\circ$ | | DWG. NO. 1-CBL-00 | |
| TWO PLACE DECIMAL $\pm .03$ | | REV 01 | |
| THREE PLACE DECIMAL $\pm .01$ | | SCALE: 1:1 | |
| INTERPRET GEOMETRIC TOLERANCING PER: | | WEIGHT: 1.66 LBS | |
| MATERIAL: 6061 Alloy | | SHEET 1 OF 1 | |
| FINISH: | | DO NOT SCALE DRAWING | |